

CASIO®

ELECTRONIC CASH REGISTER

SE-S100

A Stylish Addition To Your Store Decor



<http://www.casio-intl.com/asia-mea/en/sa/>

Use color to provide a more refined shopping experience.

A choice of exquisite colors to enhance your store's appeal. Plus all the functions you need for efficient business operation.



Easy-to-read LCD displays

Backlit LCD

The backlit two-line LCD is easy to read even in dimmed store interiors.



Customer display builds customer confidence

The rear customer display reduces check-out errors and builds customer confidence by allowing customers to confirm sales transactions.



SD card compatible

SD card data transfer for efficient operation

The use of a SD card to save / load cash register settings or save sales data on a PC supports reliable, efficient register operation.



Usable SD/SDHC cards : 2GB, 4GB, 8GB, 16GB and 32GB Class 4 or higher

High-performance thermal printer

Quiet operation and sharp, clear printing

The quiet thermal printer delivers high resolution of 384 dots per line. Drop-in paper loading makes paper roll replacement quick and easy.



Designed for optimal operability

Easy-to-use keyboard

Ergonomic design provides greater ease of use.

Helpful keys

One-touch call up of frequently used functions



<PAPER SAVING> This function is used to save printing paper (no receipt issuance and compressed journal printing).

<POST RECEIPT> In paper saving mode, receipts can be issued on demand after transactions.

<TAX PGM> This is a shortcut key to tax rate setting mode.

<HELP> This key is used to print simple guidance notes about basic settings and operations.

Multi-language support

Designed for global use, the register supports printing in English, Spanish, French, Arabic, and Vietnamese.

(The supported language differs depending on your area.)

Simple, user-friendly specifications

Other Functions

Easy initial setup

Basic settings such as language, date, time, and tax rate will automatically start when you use the machine for the first time. The main display and printer will provide step-by-step setup guidance.

Simple character setting

Characters can be easily entered from the 10-key keypad to set the department name and PLU name. The main display enables you to confirm input characters at a glance.

Electronic journal function

The Electronic Journal function enables you to save the contents of sales transactions in built-in memory.

Other functions

- Journal or receipt printing selection
- Customizable receipt message
- Calculator mode
- Secure mode key switching
- Useful multipurpose tray
- Battery backup for memory protection
(Batteries are not included with the unit.)

Specifications

No. of departments	24 departments (12 department keys x 2 shift keys)			
No. of PLUs	2,000			
Memory backup	Battery backup (Two AA batteries required)			
Display	Operator display : 2-line LCD (backlit) Customer display : 1-line LCD			
Printer	Thermal printer / Printing speed : Max 10 lines/sec.			
Power source	100V to 240V			
Power consumption	120V	220V	230V	240V
	During operation : 0.36A	0.24A	0.24A	0.24A
	When switched off : 0.03A	0.04A	0.04A	0.04A
Paper width	58mm +0/-1mm Max 80φ			
Environment	Operating temperature : 0°C to 40°C (32°F to 104°F) Humidity : 10% to 90%			
Dimensions	With small drawer : 167mm(H)×326mm(W)×345mm(D)			
	With medium drawer : 180mm(H)×410mm(W)×450mm(D)			
Weight	Approx. 3.3 kg with small drawer, 7.3 kg with medium drawer			

Color selection



SE-S100-S-GD (Gold)



SE-S100-S-SR (Silver)



SE-S100-S-RD (Red)



SE-S100-S-BK (Black)

Medium-size drawer

Also available with a medium-size drawer that holds eight types of coins and four types of banknotes



SE-S100-M-GD (Gold)



SE-S100-M-BK (Black)

Note : SD and the SD logo are trademarks of SD-3C, LLC.

Other company and product names are generally registered trademarks or trademarks of the respective companies.

Specifications in the table above are current as of February 2015 and are subject to change.

<http://www.casio-intl.com/asia-mea/en/sa/>

CASIO COMPUTER CO., LTD.
Tokyo, Japan